



SR type seal



TRL type seal

轴承代号 Bearing	轴径 Shaft Dia.	外形尺寸 (英寸) 或 (毫米) Dimensions (in) or (mm)										额定动负荷 Basic Dynamic Load Rating	额定静负荷 Basic Static Load Rating	重量 Weight										
No.	d	D	Bi	Be	n	B	i	K	H	G	ds	(N)	(N)	(Kg)										
HC 305-14	7/8	25	2.4409	1.8425	0.7874	0.6575	1.3740	0.4685	1.6850	0.6260	0.2362	5/16-24UNF M8X1.0	22800	11700	0.46									
305-15	15/16		62	46.8	20	16.7	34.9	11.9	42.8	15.9	6				0.44									
305															0.43									
305-16	1														0.43									
HC 306-18	1 1/8	30	2.8346	1.9685	0.9055	0.6890	1.4370	0.5315	1.9685	0.6890	0.2638	5/16-24UNF M8X1.0	27500	15500	0.71									
306			72	50	23	17.5	36.5	13.5	50	17.5	6.7				0.68									
306-20	1 1/4														0.68									
HC 307-20	1 1/4	35	3.1496	2.0315	0.9843	0.7205	1.5000	0.5315	2.1654	0.6890	0.2683	5/16-24UNF M8X1.0	34100	19600	0.86									
307-21	1 5/16														80	51.6	25	18.3	38.1	13.5	55	17.5	6.7	0.83
307-22	1 3/8																							0.80
307																								0.80
307-23	1 7/16																							0.78
HC 308-24	1 1/2	40	3.5433	2.2480	1.0630	0.7795	1.6260	0.6220	2.5000	0.8110	0.3150	3/8-24UNF M10X1.25	41300	24400	1.13									
308-25	1 19/16		90	57.1	27	19.8	41.3	15.8	63.5	20.6	8				1.13									
308															1.08									
308-26	1 5/8														1.57									
HC 309-26	1 5/8	45	3.9370	2.3110	1.1417	0.7795	1.6890	0.6220	2.7559	0.8110	0.3150	3/8-24UNF M10X1.25	54000	32400	1.52									
309-27	1 11/16														100	58.7	29	19.8	42.9	15.8	70	20.6	8	1.47
309-28	1 3/4																							1.47
309																								1.45
HC 310-30	1 7/8	50	4.3307	2.6220	1.2595	0.9685	1.9370	0.6850	3.0000	0.8740	0.3425	3/8-24UNF M10X1.25	63000	38500	1.93									
310-31	1 15/16														110	66.6	32	24.6	49.2	17.4	76.2	22.2	8.7	1.88
310																								1.86
310-32	2																							1.84
HC 311-32	2	55	4.7244	2.870	1.3386	1.0945	2.1890	0.6850	3.2677	0.8740	0.3543	7/16-20UNF M10X1.25	72900	45700	2.49									
311-34	2 1/8														120	73	34	27.8	55.6	17.4	83	22.2	9	2.36
311																								2.30
311-35	2 3/16																							2.24
HC 312-36	2 1/4	60	5.1181	3.1260	1.4173	1.2185	2.4370	0.6890	3.5039	0.9409	0.3543	7/16-20UNF M10X1.25	83200	52800	2.95									
312															130	79.4	36	30.95	61.9	17.5	89	23.9	9	2.89
312-38	2 3/8																							2.89
312-39	2 7/16																							2.86
HC 313-40	2 1/2	65	5.5118	3.3740	1.5354	1.2795	2.5630	0.8110	3.8189	1.0630	0.4528	7/16-20UNF M12X1.25	95700	61700	3.85									
313			140	85.7	39	32.5	65.1	20.6	97	27	11.5				3.66									
313-44	2 3/4		150	92.1	41	34.15	68.3	23.8	102	30.2	12				4.40									
HC 314-44	2 3/4	70	5.9055	3.6260	1.6142	1.3445	2.6890	0.9370	4.0157	1.1890	0.4724	1/2-20UNF M12X1.25	106300	69300	4.50									
314			180	109.5	47	42	84.1	25.4	127	31.8	13				4.50									
HC 315	75	3	6.2992	3.9370	1.6929	1.4685	2.9370	1.0000	4.4488	1.2520	0.5118	5/8-18UNF M16X1.5	115600	78300	5.34									
315-48			160	100	43	37.3	74.6	25.4	113	31.8	13				5.34									
HC 316	80	3 1/8	6.6929	4.1890	1.7717	1.5945	3.1890	1.0000	4.6850	1.2520	0.5118	5/8-18UNF M16X1.5	125300	88200	6.70									
316-50			170	106.4	45	40.5	81	25.4	119	31.8	13				6.70									
HC 317	85	3 1/4	7.0866	4.3110	1.8504	1.6535	3.3110	1.0000	5.0000	1.2520	0.5118	5/8-18UNF M16X1.5	135300	98400	8.03									
317-52			180	109.5	47	42	84.1	25.4	127	31.8	13				7.96									
HC 318-56	3 1/2	90	7.4803	4.5630	1.9291	1.7165	3.4370	1.1260	5.2362	1.4370	0.5709	3/4-16UNF M20X1.5	145900	110200	9.10									
318			190	115.9	49	43.6	87.3	28.6	133	36.5	14.5				9.10									
HC 319	95	3 3/4	7.8740	4.8150	2.0079	1.8425	3.6890	1.1260	5.5118	1.4370	0.5709	3/4-16UNF M20X1.5	159100	124400	10.40									
319-60			200	122.3	51	46.8	93.7	28.6	140	36.5	14.5				10.40									
HC 320	100	4	8.4646	5.0630	2.1654	1.9685	3.9370	1.1260	5.7480	1.4370	0.5709	3/4-16UNF M20X1.5	175100	142800	13.0									
320-64			215	128.6	55	50	100	28.6	146	36.5	14.5				13.0									