



SR type seal



TRL type seal

带座轴承代号 轴径
Bearing Unit Shaft Dia

外形尺寸 (英寸) 或 (毫米)
Dimensions(in)or(mm)

螺栓 轴承代号 座代号 重量
Bolt Used Bearing Housing Weight

No.	d	h	a	e	b	N	g	w	Bi	n	No.	No.	
	(in.) (mm)										(mm) (in.)		(kg)
UCIP 208-24	1 1/2	2 3/64	7 7/8	5 29/32	2 23/64	3/4	63/64	4 17/32	1.9370	0.7480	M16	5/8	UC208-24
208-25	1 9/16	60	200	150	60	19	25	115	49.2	19.0			208-25
208	40	60	200	150	60	19	25	115	49.2	19.0	M16	5/8	IP208
208	40	60	200	150	60	19	25	115	49.2	19.0			208
UCIP 209-27	1 11/16	2 3/4	7 7/8	6 19/24	2 23/64	3/4	63/64	5 3/64	1.9370	0.7480	M16	5/8	UC209-27
209-28	1 3/4	70	210	160	60	19	25	128	49.2	19.0			209-28
209	45	70	210	160	60	19	25	128	49.2	19.0	M16	5/8	IP209
209	45	70	210	160	60	19	25	128	49.2	19.0			209
UCIP 210-30	1 7/8	2 3/4	8 21/32	6 11/16	2 23/64	3/4	1 7/64	5 13/64	2.0315	0.7480	M16	5/8	UC210-30
210-31	1 15/16	70	220	170	60	19	28	132	51.6	19.0			210-31
210	50	70	220	170	60	19	28	132	51.6	19.0	M16	5/8	IP210
210	50	70	220	170	60	19	28	132	51.6	19.0			210
UCIP 211-32	2	3 5/32	9 1/16	7 3/32	2 23/64	3/4	1 7/64	5 53/64	2.1890	0.8740	M16	5/8	UC211-32
211-34	2 1/8	80	230	180	60	19	28	148	55.6	22.2			211-34
211	55	80	230	180	60	19	28	148	55.6	22.2	M16	5/8	IP211
211	55	80	230	180	60	19	28	148	55.6	22.2			211
211-35	2 3/16												211-35
UCIP 212-36	2 1/4	3 5/32	10 15/64	7 7/8	2 3/4	5 5/64	1 3/16	6 7/64	2.5630	1.0000	M20	3/4	UC212-36
212-38	2 3/8	80	260	200	70	22	30	155	65.1	25.4			212-38
212	60	80	260	200	70	22	30	155	65.1	25.4	M20	3/4	IP212
212	60	80	260	200	70	22	30	155	65.1	25.4			212
212-39	2 7/16												212-39
UCIP 213-40	2 1/2	3 35/64	11 4/32	8 21/32	2 3/4	5 5/64	1 3/16	6 25/32	2.5630	1.0000	M20	3/4	UC213-40
213	65	90	280	220	70	22	30	172	65.1	25.4			213
213	65	90	280	220	70	22	30	172	65.1	25.4	M20	3/4	IP212
213	65	90	280	220	70	22	30	172	65.1	25.4			213
UCIP 313	65	4 21/64	12 13/64	9 27/32	2 3/4	5 5/64	1 3/16	8 3/16	2.9528	1.1881	M20	3/4	UC313
		110	310	250	70	22	30	208	75	30			IP313
		110	310	250	70	22	30	208	75	30			IP313
		110	310	250	70	22	30	208	75	30			IP313
UCIP 314	70	4 21/64	13 10 5/8	10 5/8	2 5/8	5 5/64	1 3/8	8 15/32	3.0709	1.2992	M22	7/8	UC314
		110	330	270	75	25	35	215	78	33			IP314
		110	330	270	75	25	35	215	78	33			IP314
		110	330	270	75	25	35	215	78	33			IP314
UCIP 315	75	4 23/32	13 25/64	11 1/32	2 5/8	5 5/64	1 3/8	9 1/16	3.2283	1.2598	M22	7/8	UC315
		120	340	280	75	25	35	230	82	32			IP315
		120	340	280	75	25	35	230	82	32			IP315
		120	340	280	75	25	35	230	82	32			IP315
UCIP 316	80	4 23/32	13 25/32	11 27/64	3 11/32	5 5/64	1 37/64	9 1/4	3.3858	1.3386	M22	7/8	UC316
		120	350	290	85	25	40	235	86	34			IP316
		120	350	290	85	25	40	235	86	34			IP316
		120	350	290	85	25	40	235	86	34			IP316
UCIP 317	85	5 1/8	14 9/16	12 13/64	3 11/32	5 5/64	1 37/64	10 3/64	3.7795	1.5748	M22	7/8	UC 317
		130	370	310	85	25	40	255	96	40			IP317
		130	370	310	85	25	40	255	96	40			IP317
		130	370	310	85	25	40	255	96	40			IP317
UCIP 318	90	5 1/8	15 3/4	13	3 11/32	5 5/64	1 25/32	10 15/64	3.7795	1.5748	M24	15/16	UC318
		130	400	330	85	29	45	260	96	40			IP318
		130	400	330	85	29	45	260	96	40			IP318
		130	400	330	85	29	45	260	96	40			IP318
UCIP 319	95	5 29/32	16 9/64	13 25/64	3 11/32	5 5/64	1 25/31	11 15/64	4.0551	1.6142	M24	15/16	UC319
		150	410	340	85	29	45	285	103	41			IP319
		150	410	340	85	29	45	285	103	41			IP319
		150	410	340	85	29	45	285	103	41			IP319
UCIP 320	100	5 29/32	16 15/16	14 11/64	3 11/32	5 5/64	1 25/32	11 5/8	4.2519	1.6535	M24	15/16	UC320
		150	430	360	85	29	45	295	108	42			IP320
		150	430	360	85	29	45	295	108	42			IP320
		150	430	360	85	29	45	295	108	42			IP320
UCIP 322	110	6 11/16	19 9/64	16 9/64	3 15/16	1 17/64	1 31/32	13 3/16	4.6063	1.8110	M27	1	UC322
		170	490	410	100	32	50	335	117	46			IP322
		170	490	410	100	32	50	335	117	46			IP322
		170	490	410	100	32	50	335	117	46			IP322
UCIP 324	120	6 11/16	20 5/64	16 15/16	3 15/16	1 17/64	1 31/32	13 19/32	4.9606	2.0079	M27	1	UC324
		170	510	430	100	32	50	345	126	51			IP324
		170	510	430	100	32	50	345	126	51			IP324
		170	510	430	100	32	50	345	126	51			IP324
UCIP 326	130	7 7/8	21 21/32	18 1/2	4 21/64	1 17/64	1 31/32	15 23/64	5.3150	2.1260	M27	1	UC326
		200	550	470	110	32	50	390	135	54			IP326
		200	550	470	110	32	50	390	135	54			IP326
		200	550	470	110	32	50	390	135	54			IP326
UCIP 328	140	7 7/8	23 15/64	19 11/16	4 21/64	1 3/8	2 11/64	15 3/4	5.7086	2.3228	M30	1 1/8	UC328
		200	590	500	110	35	55	400	145	59			IP328
		200	590	500	110	35	55	400	145	59			IP328
		200	590	500	110	35	55	400	145	59			IP328