



SR type seal



TRL type seal

带座轴承代号 轴径
Bearing Unit Shaft Dia

外形尺寸 (英寸) 或 (毫米)
Dimensions(in)or(mm)

螺栓 轴承代号 座代号 重量
Bolt Used Bearing Housing Weight

No.	d	a	p	e	i	L	S	j	k	g	f	Z	Bi	n	No.	No.	(kg)	
	(in.)(mm)													(mm)(in.)				
UCFCX05-14	7/8														UC X05-14			
X05-15	15/16	4 3/8	3 5/8	2 9/16	2 5/64	1 3/16	3/8	1 5/64	3/8	1 5/16	2.9921	1 17/64	1.5000	0.6260	M8	5/16	X05-15 FCX05 1.2	
X05	25	111	92	65	10	30	9.5	6	9.5	24	76	32.2	38.1	15.9				
X05-16	1														UC X05-16			
UCFCX06-18	1 1/8														UC X06-18			
X06	30	5	4 9/64	2 59/64	5/16	1 17/64	1 5/32	3/8	3/8	7/8	3.3464	1 5/16	1.6890	0.6890	M10	3/8	X06 FCX06 1.5	
X06-19	1 3/16	127	105	74.2	8	32	12	9.5	9.5	22.5	85	33.4	42.9	17.5				
X06-20	1 1/4														UC X06-20			
UCFCX07-20	1 1/4														UC X07-20			
X07-21	1 5/16	5 1/4	4 3/8	3 3/32	2 3/64	1 29/64	1 5/32	7/16	7/16	1 1/32	3.6220	1 35/64	1.9370	0.7480	M10	3/8	X07-21 FCX07 1.9	
X07-22	1 3/8	35	133	111	78.5	9	37	12	11	11	26	92	49.2	19.0				
X07															UC X07-22			
X07-23	1 7/16														UC X07-23			
UCFCX08-24	1 1/2														UC X08-24			
X08-25	1 9/16	5 1/4	4 3/8	3 3/32	2 3/64	1 29/64	1 5/32	7/16	7/16	1 1/32	3.6220	1 35/64	1.9370	0.7480	M10	3/8	X08-25 FCX08 2.0	
X08	40	133	111	78.5	9	37	12	11	11	26	92	39.2	49.2	19.0				
UCFCX09-26	1 5/8														UC X09-26			
X09-27	1 11/16	6 3/32	5 1/8	3 5/8	5/16	1 29/64	3 5/64	1 5/32	7/16	1	4.2520	1 19/32	2.0315	0.7480	M12	7/16	X09-27 FCX09 2.6	
X09-28	1 3/4	155	130	91.9	8	37	14	12	11	25	108	40.6	51.6	19.0				
X09	45														UC X09-28			
UCFCX10-30	1 7/8														UC X10-30			
X10-31	1 5/16	6 3/8	5 23/64	3 25/32	9/32	1 5/8	3 5/64	5/8	7/16	1	4.6457	1 19/32	2.1890	0.8740	M12	7/16	X10-31 FCX10 3.2	
X10	50	162	136	96.2	7	41	14	16	11	25	118	40.4	55.6	22.2				
UCFCX11-32	2														UC X11-32			
X11-34	2 1/8	7 3/32	5 53/64	4 15/64	5/32	1 57/64	5/8	5 5/64	1/2	1 1/32	5.0000	1 23/32	2.5630	1.0000	M14	1/2	X11-34 FCX11 4.2	
X11	55	180	152	107.5	4	48	16	22	13	26	127	43.7	65.1	25.4				
X11-35	2 3/16														UC X11-35			
UCFCX12-36	2 1/4														UC X12-36			
X12	60	7 5/8	6 1/2	4 19/32	7/16	2 3/32	5/8	2 5/32	9/16	1 5/16	5.5118	2	2.5630	1.0000	M14	1/2	X12 FCX12 5.3	
X12-38	2 3/8	194	165	116.7	11	53	16	20	14	33	140	50.7	65.1	25.4				
X12-39	2 1/16														UC X12-39			
UCFCX13-40	2 1/2														UC X13-40			
X13	65	7 5/8	6 1/2	4 19/32	7/16	2 3/32	5/8	2 5/32	9/16	1 5/16	5.5118	2 3/16	2.9370	1.1890	M14	1/2	X13 FCX13 5.7	
UCFCX14-44	2 3/4														UC X14-44			
X14	70	8 3/4	7 31/64	5 9/32	3 5/64	2 7/32	3/4	2 5/32	9/16	1 27/64	6.4567	2 5/16	3.0630	1.3110	M16	5/8	X14 FCX14 7.4	
UCFCX15															UC X15			
X15-48	3	75	8 3/4	7 31/64	5 9/32	1 5/32	2 1/4	3/4	5 5/64	5/8	1 3/8	6.4567	2 13/32	3.2520	1.3110	M16	5/8	X15-48 FCX15 7.9
UCFCX16															UC X16			
X16	80	10 1/4	8 5/8	6 3/32	2 5/64	2 13/32	2 9/32	6 3/64	3/4	1 27/64	7.3228	2 27/64	3.3740	1.3425	M20	3/4	X16 FCX16 11.5	
UCFCX17-52	3 1/4														UC X17-52			
X17	85	10 1/4	8 5/8	6 3/32	2 5/64	2 13/32	2 9/32	6 3/64	3/4	1 27/64	7.3228	2 5/8	3.7795	1.5630	M20	3/4	X17 FCX17 13.0	
UCFCX18-56	3 1/2														UC X18-56			
X18	90	10 1/4	8 5/8	6 3/32	1 5/32	2 5 1/64	2 9/32	1 7/64	3/4	1 11/16	7.3228	2 7/8	4.0945	1.6890	M20	3/4	X18 FCX18 14.0	
UCFCX20															UC X20			
X20-64	4	100	10 7/8	9 3/8	6 5/8	5 5/64	3 4 5/64	2 9/32	1 7/64	5 5/64	2 19/32	8.1102	3 9/16	4.6260	1.9370	M20	3/4	X20-64 FCX20 18.1