



B type seal



A type seal

带座轴承代号 轴径 外形尺寸 (英寸) 或 (毫米) 螺栓 轴承代号 座代号 重量  
 Bearing Unit Shaft Dia Dimensions(in)or(mm) Bolt Used Bearing Housing Weight

No.	d	a	e	i	g	l	S	b	Z	Bi	n	No.	No.	
	(in.) (mm)											(mm)(in.)	(kg)	
SAFL 201 201-8	1/2	12	3 <sup>57/64</sup> 99	3 <sup>1/64</sup> 76.5	19/32 15	7/16 11	31/32 24.5	29/64 11.5	2 1/4 57	1 31/64 37.6	0.7520 19.1	0.2362 6.0	M10 3/8 SA 201 201-8	FI201 0.38
SAFL 202 202-10	5/8	15	3 <sup>57/64</sup> 99	3 <sup>1/64</sup> 76.5	19/32 15	7/16 11	31/32 24.5	29/64 11.5	2 1/4 57	1 31/64 37.6	0.7520 19.1	0.2362 6.0	M10 3/8 SA 202 202-10	FI202 0.38
SAFL 203 203-11	11/16	17	3 <sup>57/64</sup> 99	3 <sup>1/64</sup> 76.5	19/32 15	7/16 11	31/32 24.5	29/64 11.5	2 1/4 57	1 31/64 37.6	0.7520 19.1	0.2362 6.0	M10 3/8 SA 203 203-11	FI203 0.38
SAFL 204-12 204	3/4	20	4 <sup>7/16</sup> 113	3 <sup>35/64</sup> 90	19/32 15	15/32 12	1 25.5	15/32 12	2 3/8 60	1 33/64 38.4	0.8465 21.5	0.2756 7.0	M10 3/8 SA 204-12 204	FI204 0.39
SAFL 205-14 205-15 205	7/8 15/16	25	5 <sup>1/8</sup> 130	3 <sup>57/64</sup> 99	5/8 16	9/16 14	1 1/16 27	5/8 16	2 11/16 68	1 35/64 39.5	0.8465 21.5	0.2953 7.5	M14 1/2 SA 205-14 205-15 205	FI205 0.57
SAFL 206-18 206	1 1/8	30	5 <sup>13/16</sup> 148	4 <sup>39/64</sup> 117	45/64 18	9/16 14	7/32 31	5/8 16	3 5/32 80	1 49/64 44.7	0.9370 23.8	0.3150 8.0	M14 1/2 SA 206-18 206	FI206 0.83
SAFL 206-19 206-20	1 3/16 1 1/4	35	6 <sup>11/32</sup> 161	5 <sup>1/8</sup> 130	3/4 19	5/8 16	1 11/32 34	5/8 16	3 17/32 90	1 29/32 48.4	1.0000 25.4	0.3346 8.5	M14 1/2 SA 207-20 207-21 207-22 207	FI207 1.03
SAFL 207-20 207-21 207-22 207	1 1/4 1 5/16 1 3/8 1 7/16	35	6 <sup>11/32</sup> 161	5 <sup>1/8</sup> 130	3/4 19	5/8 16	1 11/32 34	5/8 16	3 17/32 90	1 29/32 48.4	1.0000 25.4	0.3346 8.5	M14 1/2 SA 207-20 207-21 207-22 207	FI207 1.03
SAFL 208-24 208-25 208	1 1/2 1 9/16	40	6 <sup>7/8</sup> 175	5 <sup>43/64</sup> 144	53/64 21	5/8 16	1 13/32 36	5/8 16	3 15/16 100	2 7/64 53.7	1.1890 30.2	0.3543 9.0	M14 1/2 SA 208-24 208-25 208	FI208 1.30
SAFL 209-26 209-27 209-28 209	1 5/8 1 1/16 1 3/4	45	7 <sup>13/32</sup> 188	5 <sup>53/64</sup> 148	55/64 22	23/32 18	1 1/2 38	3/4 19	4 1/4 108	2 5/32 54.7	1.1890 30.2	0.3740 9.5	M16 5/8 SA 209-26 209-27 209-28 209	FI209 1.86
SAFL 210-30 210-31 210	1 7/8 1 5/16	50	7 <sup>3/4</sup> 197	6 <sup>3/16</sup> 157	55/64 22	23/32 18	9/16 40	3/4 19	4 17/32 115	2 5/32 54.7	1.1890 30.2	0.3937 10.0	M16 5/8 SA 210-30 210-31 210	FI210 2.17
SAFL 211-32 211-34 211	2 2 1/8	55	8 <sup>13/16</sup> 224	7 <sup>1/4</sup> 184	63/64 25	25/32 20	1 11/16 43	3/4 19	5 1/8 130	2 27/64 61.4	1.2756 32.4	0.4724 12	M16 5/8 SA 211-32 211-34 211	FI211 2.78
SAFL 211-35 212-36 212	2 3/16 2 1/4	60	9 <sup>27/32</sup> 250	7 <sup>61/64</sup> 202	1 9/64 29	25/32 20	7/8 48	29/32 23	5 1/2 140	2 39/64 66.3	1.3150 33.4	0.4724 12	M20 3/4 SA 212-36 212 212-38 212-39	FI212 3.66