



轴承代号 Bearing	轴径 Shaft Dia-	外形尺寸 (英寸) 或 (毫米) Dimensions(in)or(mm)							额定动负荷 Basic Dynamic Load Rating	额定静负荷 Basic Static Load Rating	重量 Weight
No.	d	D	Bi	Be	n	M	G	ds	(N)	(N)	(Kg)
	(in) (mm)										
UC 305	25	2.4409	1.4961	0.7874	0.5906	0.9055	0.2362	1/4-28UNF	17600	11600	0.45
305-16	1	62	38	20	15	23	6	M6X1.0			0.44
UC 306-18	1 1/8	2.8346	1.6929	0.9055	0.6693	1.0236	0.2362	1/4-28UNF	21199	14455	0.58
306	30	72	43	23	17	26	6	M6X1.0			0.56
UC 306-20	1 1/4										
UC 307-20	1 1/4	3.1496	1.8897	0.9843	0.7480	1.1417	0.3150	5/16-24UNF	26200	18300	0.77
307-22	1 3/8	80	48	25	19	29	8	M8X1.0			0.71
307	35										0.71
UC 308-24	1 1/2	3.5433	2.0472	1.0630	0.7480	1.2992	0.3937	3/8-24UNF	32000	22800	1.05
308	40	90	52	27	19	33	10	M10X1.25			1.00
UC 309-28	1 3/4	3.9370	2.2441	1.1417	0.8661	1.3780	0.3937	3/8-24UNF	41500	30600	1.35
309	45	100	57	29	22	35	10	M10X1.25			1.33
UC 310-31	1 5/16	4.3307	2.4015	1.2595	0.8661	1.5354	0.4724	1/2-20UNF	48500	36400	1.72
310	50	110	61	32	22	39	12	M12X1.5			1.69
UC 310-32	2										
UC 311-32	2	4.7244	2.5984	1.3386	0.9842	1.6142	0.4724	1/2-20UNF	56200	42800	2.08
311	55	120	66	34	25	41	12	M12X1.5			1.90
UC 312	60	5.1181	2.7953	1.4173	1.0236	1.7717	0.4724	1/2-20UNF	64200	49600	2.60
312-36	2 1/4	130	71	36	26	45	12	M12X1.5			
UC 313-40	2 1/2	5.5118	2.9528	1.5354	1.1881	1.7717	0.4724	1/2-20UNF	73700	57800	3.24
313	65	140	75	39	30	45	12	M12X1.5			3.16
UC 314-44	2 3/4	5.9055	3.0709	1.6142	1.2992	1.7717	0.4724	1/2-20UNF	81700	64800	3.91
314	70	150	78	41	33	45	12	M12X1.5			3.90
UC 315	75	6.2992	3.2283	1.6929	1.2598	1.9685	0.5512	9/16-18UNF	89000	73100	4.70
315-48	3	160	82	43	32	50	14	M14X1.5			4.61
UC 316	80	6.6929	3.3858	1.7717	1.3386	2.0472	0.5512	5/8-18UNF	96500	83300	5.60
316-50	3 1/8	170	86	45	34	52	14	M14X1.5			
UC 317	85	7.0866	3.7795	1.8504	1.5748	2.2047	0.6299	5/8-18UNF	104100	91300	6.90
317-52	3 1/4	180	96	47	40	56	16	M16X1.5			
UC 318-56	3 1/2	7.4803	3.7795	1.9291	1.5748	2.2047	0.6299	5/8-18UNF	113000	103000	8.03
318	90	190	96	49	40	56	16	M16X1.5			7.87
UC 319	95	7.8740	4.0551	2.0079	1.6142	2.4409	0.6299	5/8-18UNF	123000	116000	8.91
		200	103	51	41	62	16	M16X1.5			
UC 320	100	8.4646	4.2519	2.1654	1.6535	2.5984	0.7087	5/8-18UNF	135800	138600	11.2
320-64	4	215	108	55	42	66	18	M18X1.5			11.0
UC 322	110	9.4488	4.6063	2.3228	1.8110	2.7953	0.7087	5/8-18UNF	205000	179000	15.1
		240	117	59	46	71	18	M18X1.5			
UC 324	120	10.2362	4.9606	2.4803	2.0079	2.9527	0.7087	5/8-18UNF	207000	185000	19.0
		260	126	63	51	75	18	M18X1.5			
UC 326		11.0236	5.3150	2.6378	2.1260	3.1890	0.7874	3/4-16UNF	229000	214000	23.6
		280	135	67	54	81	20	M20X1.5			
UC 328	140	11.8110	5.7086	2.7953	2.3228	3.3858	0.7874	3/4-16UNF	253000	246000	29.4
		300	145	71	59	86	20	M20X1.5			