



轴承代号 Bearing	轴径 Shaft Dia.	外形尺寸 (英寸) 或 (毫米) Dimensions(in)or(mm)											额定动负荷 Basic Dynamic Load Rating	额定静负荷 Basic Static Load Rating	重量 Weight
No.	d	Be	D	Bi1	n	m	Bi	K	H	G	h	ds	(N)	(N)	(Kg)
	(in)	(mm)													
SA 201	12	0.4724	1.5748	0.7520	0.2362	0.5157	1.1260	1.1260	0.5315	0.1968	0.1417	1/4-28UNF	9600	4800	0.13
201-8	1/2	12	40	19.1	6.0	13.1	28.6	28.6	13.5	5.0	3.6	M6X1.0			
SA 202	15	0.4724	1.5748	0.7520	0.2362	0.5157	1.1260	1.1260	0.5315	0.1968	0.1417	1/4-28UNF	9600	4800	0.13
202-10	8/5	12	40	19.1	6.0	13.1	28.6	28.6	13.5	5.0	3.6	M6X1.0			
SA 203	17	0.4724	1.5748	0.7520	0.2362	0.5157	1.1260	1.1260	0.5315	0.1968	0.1417	1/4-28UNF	9600	4800	0.13
203-11	11/16	12	40	19.1	6.0	13.1	28.6	28.6	13.5	5.0	3.6	M6X1.0			
SA 204-12	3/4	0.5512	1.8504	0.8465	0.2756	0.5708	1.2205	1.3110	0.5315	0.1968	0.1535	1/4-28UNF	10000	6300	0.15
204	20	14	47	21.5	7.0	14.5	31.0	33.3	13.5	5.0	3.9	M6X1.0			
SA 205-14	7/8	0.5906	2.0472	0.8465	0.2953	0.5511	1.2205	1.5000	0.5315	0.1968	0.1535	1/4-28UNF	11000	7100	0.22
205	25	15	52	21.5	7.5	14	31.0	38.1	13.5	5.0	3.9	M6X1.0			
205-16	1														
SA 206-18	1 1/8														
206	30	0.6299	2.4409	0.9370	0.3150	0.6220	1.4055	1.7520	0.6260	0.2362	0.1969	5/16-24UNF	15200	10200	0.30
206-19	1 3/16	16	62	23.8	8.0	15.8	35.7	44.5	15.9	6.0	5	M8X1.0			
206-20	1 1/4														
SA 207-20	1 1/4														
207-22	1 3/8	0.6693	2.8346	1.0000	0.3346	0.6653	1.5315	2.1890	0.6890	0.2559	0.2165	5/16-24UNF	20100	13900	0.50
207	35	17	72	25.4	8.5	16.9	38.9	55.6	17.5	6.5	5.5	M8X1.0			
207-23	1 7/16														
SA 208-24	1 1/2	0.7087	3.1496	1.1890	0.3543	0.8346	1.7205	2.3740	0.7205	0.2559	0.2362	5/16-24UNF	25600	18100	0.67
208-25	1 9/16	18	80	30.2	9.0	21.2	43.7	60.3	18.3	6.5	60	M8X1.0			
208	40														
SA 209-26	1 5/8														
209-27	1 11/16	0.7480	3.3465	1.1890	0.3740	0.8150	1.7205	2.5000	0.7205	0.2559	0.2480	5/16-24UNF	33000	21000	0.73
209-28	1 3/4	19	85	30.2	9.5	20.7	43.7	63.5	18.3	6.5	6.3	M8X1.0			
209	45														
SA 210-30	1 7/8	0.7874	3.5443	1.1890	0.3937	0.7954	1.7205	2.7520	0.7205	0.2559	0.2559	5/16-24UNF	35000	23000	0.83
210-31	1 15/16	20	90	30.2	10	20.2	43.7	69.9	18.3	6.5	6.5	M8X1.0			
210	50														
SA 211-32	2														
211-34	2 1/8	0.9449	3.9370	1.2756	0.4724	0.8032	1.9055	3.0000	0.8150	0.3150	0.2835	3/8-24UNF	44000	30000	0.87
211	55	24	100	32.4	12	20.4	48.4	76.2	20.7	8	7.2	M8X1.0			
211-35	2 3/16														
SA 212-36	2 1/4														
212	60	0.9449	4.3307	1.3150	0.4724	0.8426	2.0905	3.3150	0.8780	0.3150	0.3150	3/8-24UNF	48500	29600	1.3
212-38	2 3/8	24	110	33.4	12	21.4	53.1	84.2	22.3	8	8	M8X1.0			
212-39	2 7/16														

Note: Suffix "G" -Relub;Prefix "C" -Cylindrical O.D..