



SR type seal



TRL type seal

带座轴承代号 轴径 外形尺寸 (英寸) 或 (毫米) 螺栓 轴承代号 座代号 重量  
 Bearing Unit Shaft Dia Dimensions(in)or(mm) Bolt Used Bearing Housing Weight

No.	d	h	a	e	b	S2	S1	g	w	Bi	n	No.	No.	
(in.) (mm)												(mm) (in.) (kg)		
UCPX05		25												
X05-14	7/8	1 3/4	6 1/4	4 11/16	2	5 1/64	2 1/32	4 5/64	3 11/32	1.5000	0.6260	M14	1/2 UC X05	
X05-16	1	44.4	159	119	51	20	17	18	85	38.1	15.9		X05-14 PX05 1.50	
													X05-16	
UCPX06		30												
X06-18	1 1/8	1 7/8	6 7/8	5	2 1/4	5 1/64	2 1/32	2 5/32	3 45/64	1.689	0.689	M14	1/2 UC X06	
X06-19	1 3/16									42.9	17.5		X06-18 PX06 2.00	
X06-20	1 1/4	47.6	175	127	57	20	17	20	94				X06-19	
													X06-20	
UCPX07-20														
X07-22	1 3/8	2 1/8	8	5 21/32	2 1/4	1	2 1/32	5 5/64	4 1/8	1.9370	0.7480	M14	1/2 UC X07-20	
X07		54.0	203	144	57	25	17	22	105	49.2	19.0		X07-22 PX07 2.70	
X07-23	1 7/16												X07	
													X07-23	
UCPX08-24														
X08	1 1/2	2 5/16	8 3/4	6 5/32	2 5/8	1 1/16	2 5/32	1 1/32	4 29/64	1.9370	0.7480	M16	5/8 UC X08-24	
		58.7	222	156	67	27	20	26	113	49.2	19.0		X08 PX08 3.50	
UCPX09-26														
X09-27	1 11/16	2 5/16	8 3/4	6 5/32	2 5/8	1 1/16	2 5/32	1 1/32	4 9/16	2.0315	0.7480	M16	5/8 UC X09-26	
X09-28	1 3/4	58.7	222	156	67	27	20	26	113	51.6	19.0		X09-27 PX09 3.60	
X09													X09-28	
													X09	
UCPX10-31														
X10	1 15/16	2 1/2	9 1/2	6 23/32	2 7/8	1 3/16	2 5/32	1 1/16	4 31/32	2.1890	0.8740	M16	5/8 UC X10-31	
X10-32	2	63.5	241	171	73	30	20	27	126	55.6	22.2		X10 PX10 4.40	
													X10-32	
UCPX11														
X11-32	2	2 3/4	10 1/4	7 1/4	3 1/8	1 3/16	1	1 3/16	5 5/32	2.5630	1.0000	M20	3/4 UC X11	
X11-35	2 3/16	69.8	260	184	79	30	25	30	139	65.1	25.4		X11-32 PX11 6.30	
X11-36	2 1/4												X11-35	
													X11-36	
UCPX12														
X12-36	2 1/4	3	11 1/4	8	3 9/32	1 3/16	1	1 17/64	5 31/32	2.5630	1.0000	M20	3/4 UC X12	
X12-38	2 3/8	76.2	286	203	83	30	25	32	152	65.1	25.4		X12-36 PX12 7.40	
X12-39	2 7/16												X12-38	
													X12-39	
UCPX13-40														
X13	2 1/2	3	11 1/4	8	3 9/32	1 3/16	1	1 17/64	6 1/16	2.9370	1.1890	M20	3/4 UC X13-40	
		76.2	286	203	83	30	25	32	154	74.6	30.2		X13 PX13 7.70	
UCPX14-44														
X14	2 3/4	3 1/2	13	9 1/32	3 1/2	1 37/64	1 1/16	1 3/8	6 23/32	3.0630	1.3110	M22	7/8 UC X14-44	
		88.9	330	229	89	40	27	35	171	77.8	33.3		X14 PX14 10.60	
UCPX15														
X15-47	2 5/16	3 1/2	13	9 1/32	3 1/2	1 37/64	1 1/16	1 3/8	6 7/8	3.2520	1.3110	M22	7/8 UC X15	
X15-48	3	88.9	330	229	89	40	27	35	175	82.6	33.3		X15-47 PX15 11.10	
													X15-48	
UCPX16														
X16-50	3 1/4	4	15	11 5/32	4 1/32	1 37/64	1 1/16	1 21/32	7 11/16	3.3740	1.3425	M22	7/8 UC X16	
		101.6	381	283	102	40	27	42	195	85.7	34.1		X16-50 PX16 16.20	
UCPX17														
X17-52	3 1/4	4	15	11 5/32	4 1/32	1 37/64	1 1/16	1 49/64	7 7/8	3.7795	1.5630	M22	7/8 UC X17	
		101.6	381	283	102	40	27	45	200	96.0	39.7		X17-52 PX17 16.50	
UCPX18-56														
X18	2 1/2	4	15	11 5/32	4 3/8	1 37/64	1 1/16	1 49/64	8 1/32	4.0945	1.6890	M22	7/8 UC X18-56	
		90	101.6	381	283	111	40	27	45	204	104.0	42.9		X18 PX18 18.00
UCPX20														
X20-64	4	5	17	13 9/32	4 3/4	1 37/64	1 5/16	2 3/64	9 21/32	4.6260	1.9370	M27	1 UC X20	
		127.0	432	337	121	40	33	52	245	117.5	49.2		X20-64 PX20 31.80	