



SR type seal



TRL type seal

带座轴承代号 轴承 外形尺寸 (英寸) 或 (毫米) 螺栓 轴承代号 座代号 重量
 Bearing Unit Shaft Dia Dimensions(in)or(mm) Bolt Used Bearing Housing Weight

No.	d	a	e	i	g	l	s	Z	Bi	n	No.	No.	(kg)		
	(in.) (mm)									(mm) (in.)					
UCF 201	1/2	12	3 3/8	2 33/64	1 19/32	1 15/32	1 15/32	1 15/16	1.2205	0.5000	M10 3/8	UC 201	F201	0.63	
UCF 201-8			86	64	15	12	25.5	12	33.3	31.0	12.7	UC 201-8			
UCF 202	5/8	15	3 3/8	2 33/64	1 19/32	1 15/32	1 15/32	1 15/16	1.2205	0.5000	M10 3/8	UC 202	F202	0.63	
UCF 202-10			86	64	15	12	25.5	12	33.3	31.0	12.7	UC 202-10			
UCF 203	1 1/16	17	3 3/8	2 33/64	1 19/32	1 15/32	1 15/32	1 15/16	1.2205	0.5000	M10 3/8	UC 203	F203	0.63	
UCF 203-11			86	64	15	12	25.5	12	33.3	31.0	12.7	UC 203-11			
UCF 204-12	3/4	20	3 3/8	2 33/64	1 19/32	1 15/32	1 15/32	1 15/16	1.2205	0.5000	M10 3/8	UC 204-12	F204	0.63	
UCF 204			86	64	15	12	25.5	12	33.3	31.0	12.7	UC 204			
UCF 205-14	7/8	25	3 3/4	2 3/4	5/8	9/16	1 1/16	1 15/32	1 13/32	1.3386	0.5630	M10 3/8	UC 205-14	F205	0.82
UCF 205-15	1 5/16		95	70	16	14	27	12	35.7	34.1	14.3	UC 205-15			
UCF 205												UC 205			
UCF 205-16	1											UC 205-16			
UCF 206-18	1 1/8	30	4 1/4	3 17/64	4 5/64	9/16	1 7/32	1 15/32	1 19/32	1.5000	0.6260	M10 3/8	UC 206-18	F206	1.10
UCF 206			108	83	18	14	31	12	40.2	38.1	15.9	UC 206			
UCF 206-19	1 3/16											UC 206-19			
UCF 206-20	1 1/4											UC 206-20			
UCF 207-20	1 1/4		4 19/32	3 5/8	3/4	5/8	1 11/32	3 5/64	1 3/4	1.6890	0.6890	M12 7/16	UC 207-20		
UCF 207-21	1 5/16											UC 207-21			
UCF 207-22	1 3/8	35	117	92	19	16	34	14	44.4	42.9	17.5	UC 207-22	F207	1.50	
UCF 207												UC 207			
UCF 207-23	1 7/16											UC 207-23			
UCF 208-24	1 1/2		5 1/8	4 1/64	5 3/64	5/8	1 13/32	5/8	2 1/64	1.9370	0.7480	M14 1/2	UC 208-24	F208	1.9
UCF 208-25	1 9/16											UC 208-25			
UCF 208		40	130	102	21	16	36	16	51.2	49.2	19.0	UC 208			
UCF 209-26	1 5/8		5 13/32	4 9/64	5 5/64	2 3/32	1 1/2	5/8	2 1/16	1.9370	0.7480	M14 1/2	UC 209-26	F209	2.3
UCF 209-27	1 11/16											UC 209-27			
UCF 209-28	1 3/4											UC 209-28			
UCF 209		45	137	105	22	18	38	16	52.2	49.2	19.0	UC 209			
UCF 210-30	1 7/8		5 5/8	4 3/8	5 5/64	2 3/32	1 9/16	5/8	2 5/32	2.0315	0.7480	M14 1/2	UC 210-30	F210	2.5
UCF 210-31	1 15/16											UC 210-31			
UCF 210		50	143	111	22	18	40	16	54.6	51.6	19.0	UC 210			
UCF 210-32	2											UC 210-32			
UCF 211-32	2											UC 211-32			
UCF 211-34	1 1/8		6 3/8	5 1/8	6 3/64	2 5/32	1 11/16	3/4	2 19/64	2.1890	0.8740	M16 5/8	UC 211-34	F211	3.4
UCF 211		55	162	130	25	20	43	19	58.4	55.6	22.2	UC 211			
UCF 211-35	2 3/16											UC 211-35			
UCF 212-36	2 1/4											UC 212-36			
UCF 212		60	175	143	29	20	48	19	68.7	65.1	25.4	UC 212	F212	4.4	
UCF 212-38	2 3/8											UC 212-38			
UCF 212-39	2 1/16											UC 212-39			
UCF 213-40	2 1/2		7 3/8	5 55/64	1 3/16	2 5/32	1 31/32	3/4	2 3/4	2.5630	1.0000	M16 5/8	UC 213-40	F213	5.3
UCF 213		65	187	149	30	20	50	19	69.7	65.1	25.4	UC 213			
UCF 214-44	2 3/4		7 19/32	5 63/64	1 7/32	1 5/16	2 1/8	3/4	2 31/32	2.9370	1.1890	M16 5/8	UC 214-44	F214	6.0
UCF 214		70	193	152	31.8	24	54	19	75.4	74.6	30.2	UC 214			
UCF 215		75	217	175	36	26	63	23	87.6	85.7	34.1	UC 215			
UCF 215-47	2 15/16		6 17/64	5 11/32	1 5/16	2 13/64	3/4	3 3/32	3.0630	1.3110		UC 215-47	F215	6.6	
UCF 215-48	3											UC 215-48			
UCF 216		80	208	165	35	24	58	23	83.3	82.6	33.3	UC 216	F216	7.5	
UCF 216-50	3 1/8											UC 216-50			
UCF 217-52	3 1/4		8 21/32	6 57/64	1 27/64	1 11/32	2 15/32	2 29/32	3 7/16	3.3740	1.3425	M20 3/4	UC 217-52	F217	9.1
UCF 217		85	220	175	36	26	63	23	87.6	85.7	34.1	UC 217			
UCF 218-56	3 1/2		9 1/4	7 23/64	1 37/64	1 11/32	2 43/64	2 29/32	3 51/64	3.7795	1.5630	M20 3/4	UC 218-56	F218	11.3
UCF 218		90	235	187	41	26	68	23	96.3	96.0	39.7	UC 218			
UCF 220		100	265	210	44	25	70	27	110	108	42	UC 220	F220	14.15	