



轴承代号 Bearing	轴径 Shaft Dia.	外形尺寸 (英寸) 或 (毫米) Dimensions (in) or (mm)								额定动负荷 Basic Dynamic Load Rating	额定静负荷 Basic Static Load Rating	重量 Weight
No.	d	Be	D	Bi	n	m	G	h	ds	(N)	(N)	(Kg)
	(in) (mm)											
SB 201	12	0.4724	1.5748	0.8661	0.2362	0.6299	1.1575	0.1417	10-32UNF	7600	4500	0.10
201-8	1/2	12	40	22	6.0	16.0	4	3.5	M5X0.8			
SB 202	15	0.4724	1.5748	0.8661	0.2362	0.6299	1.1575	0.1417	10-32UNF	7600	4500	0.10
202-10	5/8	12	40	22	6.0	16.0	4	3.6	M5X0.8			
SB 203	17	0.4724	1.5748	0.8661	0.2362	0.6299	1.1575	0.1417	10-32UNF	7600	4500	0.10
203-11	11/16	12	40	22	6.0	16.0	4	3.6	M5X0.8			
SB 204-12	3/4	0.5512	1.8504	0.9843	0.2756	0.7087	0.1969	0.1535	1/4-28UNF	10000	6300	0.15
204	20	14	47	25	7.0	18.0	5	3.9	M6X1.0			
SB 205-14	7/8	0.5906	2.0472	1.0630	0.2953	0.7677	0.2165	0.1535	1/4-28UNF	11000	7100	0.18
205	25	15	52	27	7.5	19.5	5.5	3.9	M6X1.0			
SB 206-18	1 5/8									15200	10200	0.27
206	30	0.6299	2.4409	1.1811	0.3150	0.8661	0.2362	0.1969	1/4-28UNF			
206-19	1 3/16	16	62	30	8.0	22.0	6	5.0	M6X1.0			
206-20	1 1/4											
SB 207-20	1 1/4									20100	13900	0.42
207-22	1 3/8	0.6693	2.836	1.2598	0.3346	0.9252	0.2559	0.2165	5/16-24UNF			
207	35	17	72	32	8.5	23.5	6.5	5.5	M8X1.0			
SB 207-23	1 7/16									25600	18100	0.60
SB 208-24	1 1/2	0.7087	3.1496	1.3386	0.3543	0.9843	0.2756	0.2362	5/16-28UNF			
208	40	18	80	34	9.0	25.0	7.0	6.0	M8X1.0			
SB 209-26	1 5/8									32600	24500	0.80
209-27	1 11/16	0.7480	3.3465	1.6220	0.3740	1.2480	0.3228	0.2480	5/16-24UNF			
209	45	19	85	41.2	9.5	31.7	8.2	6.3	M8X1.0			
SB 210-30	1 7/8									35800	23000	0.83
210-31	1 5/16	0.7874	3.5433	1.6378	0.3937	1.2441	0.3622	0.2559	5/16-24UNF			
210	50	20	90	41.6	10.1	31.6	9.2	6.5	M8X1.0			
211-32	2											
SB 211-34	2									44000	29600	1.1
211	2 1/8	0.9449	3.9370	1.7835	0.4646	1.3189	0.3858	0.2835	5/16-24UNF			
211-35	55	24	100	45.3	11.8	3.5	9.8	7.2	M8X1.0			
212-36	2 3/16											
SB 212	60	0.9449	4.3307	2.1142	0.5866	1.5276	0.3858	0.3150	3/8-24UNF	48500	33000	1.30
212-36	2 1/4	24	110	53.7	14.9	38.8	9.8	8	M10X1.25			

Note: Suffix "G" -Relub;Prefix "C" -Cylindrical O.D..