



B type seal



A type seal

轴承代号 Bearing	轴径 Shaft Dia-	外形尺寸 (英寸) 或 (毫米) Dimensions (in) or (mm)											额定动负荷 Basic Dynamic Load Rating	额定静负荷 Basic Static Load Rating	重量 Weight
No.	d	Be	D	Bl	n	m	Bi	K	H	G	h	ds	(N)	(N)	(Kg)
	(in)	(mm)													
GRA 201	12	0.4724	1.5748	0.7520	0.2559	0.4961	1.1260	1.1260	0.5315	0.1968	0.1417	1/4-28UNF	9600	4800	0.13
RA 201-8	1/2	12	40	19.1	6.5	12.6	28.6	28.6	13.5	5.0	3.6	M6X1.0	9600	4800	0.13
GRA 202	15	0.4724	1.5748	0.7520	0.2559	0.4961	1.1260	1.1260	0.5315	0.1968	0.1417	1/4-28UNF	9600	4800	0.13
RA 202-10	8/5	12	40	19.1	6.5	12.6	28.6	28.6	13.5	5.0	3.6	M6X1.0	9600	4800	0.13
GRA 203	17	0.4724	1.5748	0.7520	0.2559	0.4961	1.1260	1.1260	0.5315	0.1968	0.1417	1/4-28UNF	9600	4800	0.13
RA 203-11	11/16	12	40	19.1	6.5	12.6	28.6	28.6	13.5	5.0	3.6	M6X1.0	9600	4800	0.13
GRA 204-12	3/4	0.5512	1.8504	0.8465	0.2953	0.5510	1.2205	1.3110	0.5315	0.1968	0.1535	1/4-28UNF	10000	6300	0.15
RA 204	20	14	47	21.5	7.5	14	31.0	33.3	13.5	5.0	3.9	M6X1.0	10000	6300	0.15
GRA 205-14	7/8	0.5906	2.0472	0.8465	0.2953	0.5511	1.2205	1.5000	0.5315	0.1968	0.1535	1/4-28UNF	11000	7100	0.22
RA 205	25	15	52	21.5	7.5	14	31.0	38.1	13.5	5.0	3.9	M6X1.0	11000	7100	0.22
205-16	1														
GRA 206-18	1 1/8														
RA 206	30	0.6299	2.4409	0.9370	0.3543	0.5826	1.4055	1.7520	0.6260	0.236	0.1969	5/16-24UNF	15200	10200	0.3
206-19	1 3/16	16	62	23.8	9.0	14.8	35.7	44.5	15.9	6.0	4	M8X1.0	15200	10200	0.3
206-20	1 1/4														
GRA 207-20	1 1/4														
RA 207-22	1 3/8	0.6693	2.8346	1.0000	0.3740	0.6260	1.5315	2.1890	0.6890	0.2559	0.2165	5/16-24UNF	20100	13900	0.50
207	35	17	72	25.4	9.5	15.9	38.9	55.6	17.5	6.5	5.5	M8X1.0	20100	13900	0.50
207-23	1 7/16														
GRA 208-24	1 1/2	0.7087	3.1496	1.1890	0.4331	0.7559	1.7205	2.3740	0.7205	0.2559	0.2362	5/16-24UNF	25600	18100	0.67
RA 208-25	1 9/16	18	80	30.2	11	19.2	43.7	60.3	18.3	6.5	6.0	M8X1.0	25600	18100	0.67
208	40														
GRA 209-26	1 5/8														
RA 209-27	1 11/16	0.8661	3.3465	1.1890	0.4331	0.759	1.7205	2.5000	0.7205	0.2559	0.2677	5/16-24UNF	33000	21000	0.73
209	45	22	85	30.2	11	19.2	43.7	63.5	18.3	6.5	6.8	M8X1.0	33000	21000	0.73
209-28	1 3/4														
GRA 210-30	1 7/8	0.7874	3.5433	1.1890	0.4331	0.7559	1.7205	2.7520	0.7205	0.2559	0.2559	5/16-24UNF	35000	23000	0.83
RA 210-31	1 15/16	20	90	30.2	11	19.2	43.7	69.9	18.3	6.5	6.5	M8X1.0	35000	23000	0.83
210	50														
GRA 211-32	2														
RA 211-34	2 1/8	0.9449	3.9370	1.2756	0.4724	0.8032	1.9055	3.0000	0.8150	0.3150	0.2835	3/8-24UNF	44000	30000	0.87
211	55	24	100	32.4	12	20.4	48.4	76.2	20.7	8	7.2	M8X1.0	44000	30000	0.87
211-35	2 3/16														
GRA 212-36	2 1/4														
RA 212	60	0.9449	4.3307	1.4646	0.5315	0.9331	2.0905	3.3150	0.8780	0.3150	0.3150	3/8-24UNF	48500	29600	1.30
212-38	2 3/8	24	110	37.2	13.5	23.7	53.1	84.2	22.3	8	8	M8X1.0	48500	29600	1.30
212-39	2 7/16														

Note: Suffix "G" -Relub