



SR type seal



TRL type seal

带座轴承代号 Bearing Unit	轴径 Shaft Dia	外形尺寸 (英寸) 或 (毫米) Dimensions(in)or(mm)											螺栓 Bolt Used	轴承代号 Bearing	座代号 Housing	重量 Weight
No.	d	a	e	i	g	l	S	b	Z	B1	n	No.	No.			
	(in.) (mm)	(mm) (in.)														(kg)
UCFL 201 201-8	1/2	12	4 7/16 113	3 5/64 90	19/32 15	15/32 12	1	15/32 12	2 3/8 60	1 5/16 33.3	1.2205 31.0	0.5000 12.7	M10 3/8	UC 201 201-8	FL201	0.49
UCFL 202 202-10	5/8	15	4 7/16 113	3 5/64 90	19/32 15	15/32 12	1	15/32 12	2 3/8 60	1 5/16 33.3	1.2205 31.0	0.5000 12.7	M10 3/8	UC 202 202-10	FL202	0.49
UCFL 203 203-11	11/16	17	4 7/16 113	3 5/64 90	19/32 15	15/32 12	1	15/32 12	2 3/8 60	1 5/16 33.3	1.2205 31.0	0.5000 12.7	M10 3/8	UC 203 203-11	FL203	0.49
UCFL 204 204-12	3/4	20	4 7/16 113	3 5/64 90	19/32 15	15/32 12	1	15/32 12	2 3/8 60	1 5/16 33.3	1.2205 31.0	0.5000 12.7	M10 3/8	UC 204 204-12	FL204	0.49
UCFL 205-14 205-15 205	7/8 15/16	25	5 1/8 130	5 7/64 99	5/8 16	9/16 14	1 1/16 27	5/8 16	2 1/16 68	1 13/32 35.7	1.3386 34.1	0.5630 14.3	M14 1/2	UC 205-14 205-15 205	FL205	0.63
UCFL 206-18 206 206-19 206-20	1 1/8 3/16 1 1/4	30	5 13/16 148	4 39/64 117	45/64 18	9/16 14	7/32 31	5/8 16	3 5/32 80	1 19/32 40.2	1.5000 38.1	0.6260 15.9	M14 1/2	UC 206-18 206 206-19 206-20	FL206	0.94
UCFL 207-20 207-21 207-22 207	1 1/4 5/16 3/8	35	6 11/32 161	5 1/8 130	3/4 19	5/8 16	1 1/32 34	5/8 16	3 17/32 90	1 3/4 44.4	1.6890 42.9	0.6890 17.5	M14 1/2	UC 207-20 207-21 207-22 207	FL207	1.2
UCFL 208-24 208-25 208	1 1/2 19/16	40	6 7/8 175	5 43/64 144	53/64 21	5/8 16	1 13/32 36	5/8 16	3 15/16 100	2 1/64 51.2	1.9370 49.2	0.7480 19.0	M14 1/2	UC 208-24 208-25 208	FL208	1.6
UCFL 209-26 209-27 209-28 209	5/8 1 1/16 3/4	45	7 13/32 188	5 53/64 148	55/64 22	23/32 18	1 1/2 38	3/4 19	4 1/4 108	2 1/16 52.2	1.9370 49.2	0.7480 19.0	M16 5/8	UC 209-26 209-27 209-28 209	FL209	1.9
UCFL 210-30 210-31 210 210-32	1 7/8 1 15/16 2	50	7 3/4 197	6 3/16 157	55/64 22	23/32 18	9/16 40	3/4 19	4 17/32 115	2 5/32 54.6	2.0315 51.6	0.7480 19.0	M16 5/8	UC 210-30 210-31 210 210-32	FL210	2.2
UCFL 211-32 211-34 211 211-35	2 2 1/8 2 3/16	55	8 13/16 224	7 1/4 184	63/64 25	25/32 20	1 1/16 43	3/4 19	5 1/8 130	2 19/64 58.4	2.1890 55.6	0.8740 22.2	M16 5/8	UC 211-32 211-34 211 211-35	FL211	3.2
UCFL 212-36 212 212-38 212-39	2 1/4 2 3/8 2 1/16	60	9 27/32 250	8 51/64 202	9/64 29	25/32 20	7/8 48	29/32 23	5 1/2 140	2 45/64 68.7	2.5630 65.1	1.0000 25.4	M20 3/4	UC 212-36 212 212-38 212-39	FL212	4.1
UCFL 213-40 213	2 1/2	65	10 5/32 258	8 17/64 210	3/16 30	15/16 24	31/32 50	29/32 23	6 3/32 155	2 3/4 69.7	2.5630 65.1	1.0000 25.4	M20 3/4	UC 213-40 213	FL213	5.1
UCFL 214-44 214	2 3/4	70	10 7/16 265	8 1/2 216	1 1/4 31.8	15/16 24	2 1/8 54	29/32 23	6 5/16 160	2 31/32 75.4	2.9370 74.6	1.1890 30.2	M20 3/4	UC 214-44 214	FL214	5.9
UCFL 215 215-48	3	75	10 13/16 275	8 55/64 225	1 1/32 35	15/16 24	2 13/64 56	29/32 23	6 1/2 165	3 3/32 78.5	3.0630 77.8	1.3110 33.3	M20 3/4	UC 215 215-48	FL215	6.4
UCFL 216 216-50	3 1/8	80	11 13/32 290	9 11/64 233	1 1/32 35	15/16 24	2 9/32 58	63/64 25	7 3/32 180	3 9/32 83.3	3.2520 82.6	1.3110 33.3	M22 7/8	UC 216 216-50	FL216	7.9
UCFL 217-52 217	3 1/4	85	12 12 305	9 49/64 248	27/64 36	1 1/32 26	2 15/32 63	63/64 25	7 15/32 190	3 7/16 87.6	3.3740 85.7	1.3425 34.1	M22 7/8	UC 217-52 217	FL217	9.6
UCFL 218-56 218	3 1/2	90	12 19/32 320	10 7/16 265	37/16 41	1 1/32 26	2 43/64 68	63/64 25	8 1/16 205	3 51/64 96.3	3.7795 96.0	1.5630 39.7	M22 7/8	UC 218-56 218	FL218	12.1