



立式座 Pillow Block Housing

表7 Table7

座的代号 Housings No.	偏差 Deviations	
	H	IP,PA J
P204-P210 PA204-PA210 PH204-PH210 PG204-PG208 PX05-PX09 P305-P310 IP208-IP210 LP201-LP207	± 150	± 700
P211-P218 PA211-PA218 PH211-PH218 PX10-PX18 P311-P319 IP211-IP213 IP313-IP319	± 200	± 1000
P320-P328 IP320-IP328	± 300	

注：H 安装表面到轴中心的高度。
Notes:H-Height of mounting surface to shaft centerline

2.3 法兰型座的公差
Tolerances for flange type tolerance

表8 Table8

法兰座 Flange Unit Housings

座的代号 Housings No.				偏差 Deviations		凸台外径径向 跳动(最大) Radial runout of spigot joint(max.)	偏差 f Deviations							
F.FL.FS FC.FT	F.FL.FS	F.FL.FC	LF FD	J	A2		FC200		FC300		FCX00			
							上差 High	下差 Low	上差 High	下差 Low	上差 High	下差 Low		
204 205 206	305 306	X05 X06	204 205 206	± 700	± 500	200	0	-46	0	-46	0	-46		
207 208 209	307 308 309	X07 X08 X09	207				0	-54	0	-54	0	-54		
210 211 212	310 311 312	X10 X11 X12					0	-63	0	-63				
213 214 215	313 314 315	X13 X14 X15		± 1000	± 800	300	0	-63			0	-63		
216 217 218	316 317 318	X16 X17 X18					0	-72	0	-72			0	-72
	319 320 322	X19 X20											0	-72
	324 326 328					400			0	-81				
									0	-89				

注(Notes):

- J-孔中心距
- A2-安装表面到轴承中心线间距离
- f-凸台外径尺寸