



SR type seal



TRL type seal

带座轴承代号 Bearing Unit	轴径 Shaft Dia	外形尺寸 (英寸) 或 (毫米) Dimensions (in) or (mm)							额定动负荷 Basic Dynamic Load Rating	额定静负荷 Basic Static Load Rating	重量 Weight
No.	d	D	Bi	Be	n	M	G	ds	(N)	(N)	(Kg)
	(in) (mm)										
UC X05	25	2.4409	1.5000	0.7480	0.6260	0.8740	0.2362	1/4-28UNF M6X1.0	15200	10200	0.38
X05-16	1	62	38.1	19	15.9	22.2	6.0				0.37
UC X06	30	2.8346	1.6890	0.7874	0.6890	1.0000	0.2559	5/16-24UNF M8X1.0	20100	13900	0.55
X06-19	1 3/16	72	42.9	20	17.5	25.4	6.5				0.54
X06-20	1 1/4										0.52
UC X07-20	1 1/4										0.79
X07-22	1 3/8	3.1496	1.9370	0.8268	0.7480	1.1890	0.3150	5/16-24UNF M8X1.0	25600	16100	0.73
X07	35	80	49.2	21	19.0	30.2	8.0				0.72
X07-23	1 7/16										0.69
UC X08-24	1 1/2	3.3465	1.9370	0.8661	0.7480	1.1890	0.3150	5/16-24UNF M8X1.0	26500	19100	0.84
X08	40	85	49.2	22	19.0	30.2	8.0				0.80
X09-27	1 11/16										0.96
UC X09-28	1 3/4	3.5433	2.0315	0.9449	0.7480	1.2835	0.3937	3/8-24UNF M10X1.0	27500	20200	0.92
X09	45	90	51.6	24	19.0	32.6	10				0.90
UC X10-31	1 15/16	3.9370	2.1890	0.9843	0.8740	1.3150	0.3937	3/8-24UNF M10X1.0	34000	25500	1.22
X10	50	100	55.6	25	22.2	33.4	10				1.20
X10-32	2										1.17
UC X11	55										1.67
X11-32	2	4.3307	2.5630	1.0630	1.0000	1.5630	0.3937	3/8-24UNF M10X1.0	41000	31500	1.85
X11-35	2 3/16	110	65.1	27	25.4	39.7	10				1.65
X11-36	2 1/4										1.58
UC X12	60										2.04
X12-36	2 1/4	4.7244	2.5630	1.1024	1.0000	1.5630	0.3937	3/8-24UNF M10X1.0	44800	34700	2.18
X12-38	2 3/8	120	65.1	28	25.4	39.7	10				2.03
X12-39	2 7/16										1.95
UC X13-40	2 1/2	4.9213	2.9370	1.1811	1.1890	1.7480	0.4724	7/16-20UNF M12X1.5	48700	38100	2.38
X13	65	125	74.6	30	30.2	44.4	12.0				2.30
UC X14-44	2 3/4	5.1181	3.0630	1.1811	1.3110	1.7520	0.4724	7/16-20UNF M12X1.5	51900	41900	2.54
X14	70	130	77.8	30	33.3	44.5	12.0				2.53
UC X15	75	5.5118	3.2520	1.2992	1.3110	1.9410	0.5512	7/16-20UNF M12X1.5	57000	45500	3.41
X15-47	2 15/16	140	82.6	33	33.3	49.3	14.0				3.32
X15-48	3										
UC X16	80	5.9055	3.3740	1.3780	1.3425	2.0315	0.5511	7/16-20UNF M12X1.5	66000	53200	3.87
X16-50	3 1/8	150	85.7	35	34.1	51.6	14.0				
UC X17	85	6.2992	3.7795	1.4567	1.5630	2.2165	0.5906	7/16-20UNF M12X1.5	75500	61700	5.05
X17-52	3 1/4	160	96.0	37	39.7	56.3	15.0				
UC X18-56	3 1/2	6.6929	4.0945	1.5354	1.6890	2.4055	0.6299	1/2-20UNF M14X1.5	109000	81700	6.12
X18	90	170	104.0	39	42.9	61.1	16.0				6.00
UC X20	100	7.4803	4.6260	1.7323	1.9370	2.68909	0.7087	5/8-18UNF M16X1.5	133000	105000	8.56
X20-64	4	190	117.5	44	49.2	68.3	18.0				8.33