



轴承代号 Bearing	轴径 Shaft Dia.	外形尺寸 (英寸) 或 (毫米) Dimensions(in)or(mm)										额定动负荷 Basic Dynamic Load Rating	额定静负荷 Basic Static Load Rating	重量 Weight
No.	d	D	Bi	Be	n	m	l	K	H	G	ds	(N)	(N)	(Kg)
	(in)	(mm)												
HC 203	17	1.5748	1.4685	0.5512	0.5472	0.5472	0.3740	1.1260	0.5315	0.1968	1/4-28UNF	9000	5100	0.25
203-11	11/16	40	37.3	14	13.9	13.9	9.5	28.6	13.5	5.0	M6X1			
HC 204-12	20	1.8504	1.7205	0.6299	0.6732	0.6732	0.3740	1.3110	0.5315	0.1968	1/4-28UNF	10100	6300	0.23
204	3/4	47	43.7	16	17.1	17.1	9.5	33.3	13.5	5.0	M6X1			0.22
HC 205-14	25	2.0472	1.7441	0.6693	0.6850	0.6850	0.3740	1.5000	0.5315	0.1968	1/4-28UNF	11000	7100	0.29
205-15	15/16	52	44.3	17	17.4	17.4	9.5	38.1	13.5	5.0	M6X1			0.27
205	1													0.25
205-16	1													0.25
HC 206-18	30	2.4409	1.9055	0.7480	0.7205	0.7165	0.4685	1.7520	0.6260	0.2362	5/16-24UNF	15300	10200	0.43
206	1 1/8	62	48.4	19	18.3	18.2	11.9	44.5	15.9	6.0	M8X1			0.41
206-19	1 3/16													0.41
206-20	1 1/4													0.38
HC 207-20	35	2.8346	2.0118	0.7874	0.7402	0.7402	0.5315	2.1890	0.6890	0.2559	5/16-24UNF	20200	13900	0.68
207-22	1 3/8	72	51.1	20	18.8	18.8	13.5	55.6	17.5	6.5	M8X1			0.61
207	1 7/16													0.61
207-23	1 7/16													0.58
HC 208-24	40	3.1496	2.2165	0.8268	0.8425	0.8425	0.5315	2.3740	0.7205	0.2559	5/16-24UNF	22800	16000	0.83
208	1 1/2	80	56.3	21	21.4	21.4	13.5	60.3	18.3	6.5	M8X1			0.79
209-26	1 5/8													0.78
HC 209-26	45	3.3465	2.2165	0.8661	0.8425	0.8425	0.5315	2.5000	0.7205	0.2559	5/16-24UNF	25700	20200	0.96
209-27	1 11/16	85	56.3	22	21.4	21.4	13.5	63.5	18.3	6.5	M8X1			0.91
209-28	1 3/4													0.87
209	1 5/8													0.85
HC 210-31	50	3.5433	2.4685	0.9449	0.9685	0.9685	0.5315	2.7520	0.7205	0.2559	5/16-24UNF	27500	20200	1.04
210	1 15/16	90	62.7	24	24.6	24.6	13.5	69.9	18.3	6.5	M8X1			1.01
210-32	2													
HC 211-32	55	3.9370	2.8110	0.9843	1.0940	1.0906	0.6260	3.0000	0.8150	0.3150	3/8-24UNF	34000	25500	1.58
211	2	100	71.4	25	27.8	27.7	15.9	76.2	20.7	8.0	M10X1.25			1.39
211-35	2 3/16													1.36
HC 212-36	60	4.3307	3.0630	1.0630	1.2200	1.2165	0.6260	3.3150	0.8780	0.3150	3/8-24UNF	41000	31500	2.03
212	2 1/4	110	77.8	27	31.0	30.9	15.9	84.2	22.3	8.0	M10X1.25			1.87
212-39	2 7/16													1.76
HC 213-40	65	4.7244	3.3740	1.1024	1.3425	1.3580	0.6732	3.3858	0.9252	0.3346	3/8-24UNF	45000	34700	2.24
213	2 1/2	120	85.7	28	34.1	34.5	17.1	86	23.5	8.5	M10X1.25			
HC 214-44	70	4.9213	3.3779	1.2992	1.3441	1.3464	0.6889	3.8189	0.9252	0.3346	3/8-24UNF	49000	39500	2.36
214	2 3/4	125	85.8	33	34.1	34.2	17.5	97	23.5	8.5	M10X1.25			
HC 215-47	75	5.1181	3.6260	1.3386	1.4685	1.4840	0.6732	4.0157	0.9252	0.3346	3/8-24UNF	53000	42000	2.74
215	2 15/16	130	92.1	34	37.3	37.7	17.1	102	23.5	8.5	M10X1.25			
215-48	3													
HC 216-50	80	5.5118	3.7440	1.3780	1.4685	1.4685	0.6070	4.3307	1.0629	0.4055	7/16-20UNF	58100	46000	3.33
216	3 1/8	140	95.1	35	37.3	37.3	20.5	110	27	10.3	M12X1.5			
HC 218-56	90	6.2992	2.8543	1.4567	0.9645	1.2007	0.6889	4.7244	0.9448	0.3740	7/16-20UNF	76300	62300	3.90
218	3 1/2	160	72.5	37	24.5	30.5	17.5	120	24	9.5	M12X1.5			